

EVINRUDE® E-TEC®

135 H.O.

SPECIFICATIONS

Engine Type	H.O. V6 60° E-TEC D.I.
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)
Displacement - cu in (L)	158.2 (2.6)
Full Throttle RPM Range	5400-6000 RPM
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	133 Amps Total / 50 Net Dedicated
Steering	Remote
Trim Method	FasTrak™ Power Trim and Tilt
Trim Range	-6° to 15°
Tilt Range	75°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	Accessory 1.8 (6.8) 3 (11.3) & 10 (37.85) Tank Available
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	MODEL NO.	WEIGHT - lb (kg)	GEAR RATIO
Graphite	20 (508)	E135HGL	418 (190)	1.86:1
	25 (635)	E135HGX	433 (196)	1.85:1
White	20 (508)	E135HSL	418 (190)	1.86:1
	25 (635)	E135DHX	433 (196)	1.85:1

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp. Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE®