140 HP

SPECIFICATIONS

Engine Type	Inline 3-Cylinder E-TEC G2 D.I.			
Bore x Stroke - in (mm)	3.85 x 3.25 (98 x 82.6)			
Displacement - cu in (L)	114 (1.9)			
Gear Ratio	2.08:1			
Full Throttle RPM Range	5000-6000 RPM			
Starting	Electric			
Controls	ICON II Digital Shift and Throttle / Optional Digital Tiller			
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode			
Alternator Output - Amps*	30 Total / 22 @ Wide Open Throttle / 14 @ Idle			
Trim Method	Power Trim & Tilt			
Trim Range	-6° to 15°			
Tilt Range	81°			
Lubrication	Multi-Point Targeted Oiling			
Oil Tank Capacity - gal (L)	1.9 (7.2)			
Recommended Oil	XPS Marine XD100			
Recommended Fuel	87 Octane			
Warranty	5-Year Non-Declining** / 5-Year Corrosion			
Mounting Centers - in (mm)	Minimum 26 (660)			
Engine Color	Slate Gray or Classic White			
Panel Customization	Unlimited			
Integrated Features	Dual Axis Rigging / iTrim			
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union			



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Single —	Slate Gray	20 (508)	iSteer DPS	K140GLF	415 (188)
			Remote	K140GLP	390 (177)
		25 (635)	Remote	K140GXP	401 (182)
	Classic White	20 (508)	iSteer DPS	K140WLF	415 (188)
			Remote	K140WLP	390 (177)
		25 (635)	Remote	K140WXP	401 (182)
Single [†] /	Slate Gray	25 (635)	iSteer DPS	K140GXF ⁺	426 (193)
			Remote / Tiebar	K140GXC‡	401 (182)
Multiple	Classic White	25 (635)	iSteer DPS	K140WXF ⁺	426 (193)
			Remote / Tiebar	K140WXC [‡]	401 (182)



^{*} Current amp calculated at 13.5 $\rm V.$

^{**3} years of BRP Limited Warranty and 2 years extension. This BRP Limited Warranty Extension Program adds 24 months of coverage to the standard 36 month BRP Warranty applicable to Evinrude outboard motors under specific conditions. Offered only by BRP European Distribution SA and BRP authorized dealers for Evinrude outboard motors sold to people residing in the European Union only for recreational purposes..

[†] Standard Rotation iSteer DPS model available for single and multiple installation.

[‡] Corresponding Counter Rotation model. Specifications subject to change.