## 200 H.O.

## **SPECIFICATIONS**

| Engine Type                     | H.O. V6 74° E-TEC G2 D.I.   |
|---------------------------------|---|
| Bore x Stroke - in (mm)         | 3.85 x 3.00 (98 x 76)   |
| Displacement - cu in (L)        | 210 (3.4L)  |
| Gear Ratio                      | 1.85:1  |
| Full Throttle RPM Range         | 5400-6000 RPM   |
| Starting                        | Electric  |
| Controls                        | ICON II Digital Shift and Throttle                                |
| Fuel Induction                  | E-TEC Direct Injection with<br>Stratified Low RPM Combustion Mode |
| Alternator Output - Amps*       | 133 Total / 50 ର Wide Open Throttle / 14 ର Idle                   |
| Trim Method                     | Power Trim & Tilt   |
| Trim Range                      | -6° to 15°  |
| Tilt Range                      | 81°   |
| Lubrication                     | Multi-Point Targeted Oiling                                       |
| Oil Tank Capacity - gal (L)     | On-Engine 2 (7.5) /<br>Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85) |
| Recommended Oil                 | XPS Marine XD100  |
| Recommended Fuel                | 87 Octane   |
| Warranty                        | 5-Year Non-Declining** / 5-Year Corrosion                         |
| Mounting Centers - in (mm)      | Minimum 28 (711)  |
| Engine Color                    | Slate Gray or Classic White                                       |
| Color Customization             | Unlimited   |
| Integrated Features             | Dual Axis Rigging / iTrim   |
| 100% Global Emissions Compliant | EPA 2013 / CARB 3 STAR / European Union                           |



| INSTALLATION          | COLOR         | SHAFT LENGTH - in. (mm) | STEERING                   | MODEL NO.                                      | WEIGHT - lb (kg)       |
|-----------------------|---------------|-------------------------|----------------------------|--|------------------------|
| Single –              | Slate Gray    | 20 (508)                | iSteer DPS                 | H200HGLF                                       | 547 (248)              |
|                       | Classic White | 20 (508)                | iSteer DPS                 | H200HWLF                                       | 547 (248)              |
| Single† /<br>Multiple | Slate Gray    | 05 ((05)                | iSteer DPS<br>IHS / Tiebar | H200HGXF <sup>†</sup><br>H200HGXC <sup>‡</sup> | 569 (258)<br>558 (253) |
|                       |               | 25 (635) —              | iDOCK<br>iDOCK             | H200HGXA<br>H200GXCA‡                          | 569 (258)<br>569 (258) |
|                       |               |                         | iSteer DPS<br>IHS / Tiebar | H200HWXF <sup>†</sup><br>H200HWXC <sup>‡</sup> | 569 (258)<br>558 (253) |
|                       | Classic White | 25 (635)                | iDOCK<br>iDOCK             | H200HWXA<br>H200WXCA‡                          | 569 (258)<br>569 (258) |

‡ Corresponding Counter Rotation model. Specifications subject to change.



<sup>\*</sup> Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

<sup>\*\* 3</sup> years of BRP Limited Warranty and 2 years extension. This BRP Limited Warranty Extension Program adds 24 months of coverage to the standard 36 month BRP Warranty applicable to Evinrude outboard motors under specific conditions. Offered only by BRP European Distribution SA and BRP authorized dealers for Evinrude outboard motors sold to people residing in the European Union only for recreational purposes...

<sup>†</sup> Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK models available for multiple installation only.