

EVINRUDE® E-TEC® G2®

200 HP

SPECIFICATIONS

Engine Type	V6 66° E-TEC G2 D.I.
Bore x Stroke - in (mm)	3.39 x 3.10 (86 x 78.7)
Displacement - cu in (L)	167 (2.6L)
Gear Ratio	2.17:1
Full Throttle RPM Range	5000-6000 RPM
Starting	Electric
Controls	ICON II Digital Shift and Throttle
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	133 Total / 50 @ Wide Open Throttle / 14 @ Idle
Trim Method	Power Trim & Tilt
Trim Range	-6° to 15°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	On-Engine 3 (11.4) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
Recommended Oil	XPS Marine XD100
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining** / 5-Year Corrosion
Mounting Centers - in (mm)	Minimum 26 (660)
Engine Color	Slate Gray or Classic White
Color Customization	Unlimited
Integrated Features	Dual Axis Rigging / iTrim
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)	TILT RANGE
Single	Slate Gray	20 (508)	iSteer DPS	C200GLF	530 (240)	81°
			Remote	C200GLP	496 (225)	75°
	Classic White	20 (508)	iSteer DPS	C200WLF	530 (240)	81°
			Remote	C200WLP	496 (225)	75°
Single / Multiple	Slate Gray	25 (635)	iSteer DPS	C200GXF†	541 (245)	81°
			IHS / Tiebar	C200GXC‡	533 (242)	
			Remote	C200GXP†	507 (230)	75°
			Tiebar / Remote	C200GXCP‡	507 (230)	
			iDOCK	C200GXA	541 (245)	81°
			iDOCK	C200GXCA‡	533 (242)	
	Classic White	25 (635)	iSteer DPS	C200WXF†	541 (245)	81°
			IHS / Tiebar	C200WXC‡	533 (242)	
			Remote	C200WXP†	507 (230)	75°
			Tiebar / Remote	C200WXCP‡	507 (230)	
			iDOCK	C200WXA	541 (245)	81°
			iDOCK	C200WXCA‡	533 (242)	

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

** 3 years of BRP Limited Warranty and 2 years extension. This BRP Limited Warranty Extension Program adds 24 months of coverage to the standard 36 month BRP Warranty applicable to Evinrude outboard motors under specific conditions. Offered only by BRP European Distribution SA and BRP authorized dealers for Evinrude outboard motors sold to people residing in the European Union only for recreational purposes.

† Standard Rotation iSteer DPS and Remote models available for single and multiple installation. All iDOCK models available for multiple installation only.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2020 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

