

EVINRUDE® E-TEC® G2®

250 H.O.

SPECIFICATIONS

Engine Type	H.O. V6 74° E-TEC G2 D.I.
Bore x Stroke - in (mm)	3.85 x 3.00 (98 x 76)
Displacement - cu in (L)	210 (3.4L)
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Starting	Electric
Controls	ICON II Digital Shift and Throttle
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode
Alternator Output - Amps*	133 Total / 50 @ Wide Open Throttle / 14 @ Idle
Trim Method	Power Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	On-Engine 2 (7.5) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
Recommended Oil	XPS Marine XD100
Recommended Fuel	87 Octane
Warranty	5-Year Non-Declining** / 5-Year Corrosion
Mounting Centers - in (mm)	Minimum 28 (711)
Engine Color	Slate Gray or Classic White
Color Customization	Unlimited
Integrated Features	Dual Axis Rigging / iTrim
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Single	Slate Gray	20 (508)	IHS	H250HGLO	537 (244)
			iSteer DPS	H250HGLF	547 (248)
	Classic White	20 (508)	iSteer DPS	H250HWLF	547 (248)
Single+ / Multiple	Slate Gray	25 (635)	iSteer DPS	H250HGXF†	569 (258)
			IHS / Tiebar	H250HGXC‡	558 (253)
			iDOCK	H250HGXA	569 (258)
	Classic White	25 (635)	iDOCK	H250GXCA‡	569 (258)
			iSteer DPS	H250HWXF†	569 (258)
			IHS / Tiebar	H250HWXC‡	558 (253)
			iDOCK	H250HWXA	569 (258)
			iDOCK	H250WXCA‡	569 (258)

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

** 3 years of BRP Limited Warranty and 2 years extension. This BRP Limited Warranty Extension Program adds 24 months of coverage to the standard 36 month BRP Warranty applicable to Evinrude outboard motors under specific conditions. Offered only by BRP European Distribution SA and BRP authorized dealers for Evinrude outboard motors sold to people residing in the European Union only for recreational purposes.

† Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK models available for multiple installation only.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2020 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

