250 HP

SPECIFICATIONS

V6 74° E-TEC G2 D.I.
3.85 x 3.00 (98 x 76)
210 (3.4L)
1.85:1
5400-6000 RPM
Electric
ICON II Digital Shift and Throttle
E-TEC Direct Injection with Stratified Low RPM Combustion Mode
133 Total / 50 \odot Wide Open Throttle / 14 \odot Idle
Power Trim & Tilt
-6° to 15°
81°
Multi-Point Targeted Oiling
On-Engine 2 (7.5) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
XPS Marine XD100
87 Octane
5-Year Non-Declining** / 5-Year Corrosion
Minimum 28 (711)
Slate Gray or Classic White
Unlimited
Dual Axis Rigging / iTrim
EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Single†/ Multiple	Slate Gray	25 (635)	iSteer DPS IHS / Tiebar	H250GXF [†] H250GXC [‡]	569 (258) 558 (253)
		25 (635)	iSteer DPS IHS / Tiebar Optimus 360 / IHS IHS / Tiebar	H250WXC‡ H250WXC H250WXI H250WXC‡	569 (258) 558 (253) 558 (253) 558 (253)
	Classic White	30 (762)	iSteer DPS IHS / Tiebar Optimus 360 / IHS IHS / Tiebar	H250WZF† H250WZC‡ H250WZI H250WZC‡	538 (233) 569 (258) 570 (259) 570 (259) 570 (259)



^{*} Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

^{** 3} years of BRP Limited Warranty and 2 years extension. This BRP Limited Warranty Extension Program adds 24 months of coverage to the standard 36 month BRP Warranty applicable to Evinrude outboard motors under specific conditions. Offered only by BRP European Distribution SA and BRP authorized dealers for Evinrude outboard motors sold to people residing in the European Union only for recreational purposes...

[†] Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK and Optimus 360 models available for multiple installation only.

[‡] Corresponding Counter Rotation model. Specifications subject to change.