## 300 HP

## **SPECIFICATIONS**

Engine Type	V6 74° E-TEC G2 D.I.			
Bore x Stroke - in (mm)	3.85 x 3.00 (98 x 76)			
Displacement - cu in (L)	210 (3.4L)			
Gear Ratio	1.85:1			
Full Throttle RPM Range	5400-6000 RPM			
Starting	Electric			
Controls	ICON II Digital Shift and Throttle			
Fuel Induction	E-TEC Direct Injection with Stratified Low RPM Combustion Mode			
Alternator Output - Amps*	133 Total / 50 ର Wide Open Throttle / 14 ର Idle			
Trim Method	Power Trim & Tilt			
Trim Range	-6° to 15°			
Tilt Range	81°			
Lubrication	Multi-Point Targeted Oiling			
Oil Tank Capacity - gal (L)	On-Engine 2 (7.5) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)			
Recommended Oil	XPS Marine XD100			
Recommended Fuel	87 Octane			
Warranty	5-Year Non-Declining** / 5-Year Corrosion			
Mounting Centers - in (mm)	Minimum 28 (711)			
Engine Color	Slate Gray or Classic White			
Color Customization	Unlimited			
Integrated Features	Dual Axis Rigging / iTrim			
100% Global Emissions Compliant	t EPA 2013 / CARB 3 STAR / European Union			



NSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg
Single ———	Slate Gray	20 (508)	iSteer DPS	H300GLF	547 (248)
	Classic White	20 (508)	iSteer DPS	H300WLF	547 (248)
Single† / Multiple	Slate Gray	25 (635) –	iSteer DPS	H300GXF <sup>†</sup>	569 (258)
			IHS / Tiebar	H300GXC <sup>‡</sup>	558 (253)
			iDOCK	H300GXA	569 (258)
			iDOCK	H300GXCA <sup>‡</sup>	569 (258)
		- 25 (635) -	iSteer DPS	H300WXF <sup>†</sup>	569 (258)
			IHS / Tiebar	H300WXC <sup>‡</sup>	558 (253)
			Optimus 360 / IHS	H300WXI	558 (253)
			IHS / Tiebar	H300WXC <sup>‡</sup>	558 (253)
			iDOCK	H300WXA	569 (258)
	Ol : - \\//- : + -		iDOCK	H300WXCA <sup>‡</sup>	569 (258)
	Classic White —	30 (762)	iSteer DPS	H300WZF <sup>+</sup>	580 (263)
			IHS / Tiebar	H300WZC <sup>‡</sup>	570 (259)
			Optimus 360 / IHS	H300WZI	570 (259)
			IHS / Tiebar	H300WZC <sup>‡</sup>	570 (259)
			iDOCK	H300WZA	580 (263)
			iDOCK	H300WZCA <sup>‡</sup>	580 (263)

<sup>\*</sup> Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.



<sup>\*\* 3</sup> years of BRP Limited Warranty and 2 years extension. This BRP Limited Warranty Extension Program adds 24 months of coverage to the standard 36 month BRP Warranty applicable to Evinrude outboard motors under specific conditions. Offered only by BRP European Distribution SA and BRP authorized dealers for Evinrude outboard motors sold to people residing in the European Union only for recreational purposes...

<sup>†</sup> Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK and Optimus 360 models available for multiple installation only.

<sup>‡</sup> Corresponding Counter Rotation model. Specifications subject to change.